

CUSTOM DESIGN OPTIONS

PARAMETERS	RF CUSTOM INDUCTORS	RF CUSTOM TRANSFORMERS	POWER CUSTOM INDUCTORS	POWER CUSTOM TRANSFORMERS
MATERIALS				
Ferrites	✓	✓	✓	✓
Powdered Irons	✓	✓	✓	✓
Kool Mu™	✓	✓	✓	✓
Phenolics	✓		✓	✓
MPP		✓	✓	✓
High-Flux			✓	✓
THERMAL CLASSES				
Compliance to NEMA	✓	✓	✓	✓
Temperature Ratings to 200°C	✓	✓	✓	✓
WIRE SIZES AND STYLES				
Wire sizes up to 49 AWG	✓	✓	✓	✓
Single & Multi Strand	✓	✓	✓	✓
FREQUENCY RANGES				
250 kHz - 1.8 GHz	✓	✓		
1 kHz - 2 MHz			✓	✓
MOUNTINGS				
Surface Mount	✓	✓	✓	✓
Thru-Hole	✓	✓	✓	✓
HEADERS				
Ceramic	✓	✓	✓	✓
FR4	✓	✓	✓	✓
G10	✓	✓	✓	✓
Molded	✓	✓	✓	✓
Self-Leaded	✓	✓	✓	✓
Standard-off-the-shelf			✓	✓
ENCAPSULANTS				
Potting	✓	✓	✓	✓
Vacuum Impregnation	✓	✓	✓	✓
Varnish Coating	✓	✓	✓	✓
Thermal Set Epoxy Overmold	✓		✓	