



Contact: Denis Kohlhagen,  
Director of Sales  
716-532-2234; fax 716-532-2702  
dkohlhagen@gowanda.com  
www.gowanda.com

## Gowanda Electronics' Power Inductors Achieve Highest Level of Certification

### “MLP” Series First to be Approved for Qualified Products Listing to MIL-PRF-27 Level T

22 February 2012, Gowanda, NY (USA) - Gowanda Electronics, a US-based designer and manufacturer of precision electronic components for power, radio frequency (RF), and high frequency (HF) applications, has achieved the highest level of certification on three surface mount power inductor series. Gowanda's three “MLP” series have been added to the military's Defense Logistics Agency (DLA) Land and Maritime Qualified Products List (QPL) for MIL-PRF-27 Level T. This is the highest quality level attainable per the Department of Defense military specification MIL-PRF-27 for components used in high-reliability critical military applications. Gowanda is the first in the industry to offer these Level T components.

Gowanda's MLP5025-T series is qualified to MIL-PRF-27/367A while the company's MLP1812-T series meets MIL-PRF-27/368A and the MLP8527-T series meets MIL-PRF-27/370A. By achieving Level T certification on these wirewound molded power inductors, Gowanda is responding to a need conveyed by organizations in the military market for a high-reliability QPL-approved inductor supplier for this mil spec.

These MLP series are designed for power applications in military, space, aerospace and defense communities. This includes use in communication, guidance, and security applications, as well as in radar, test & evaluation, and special mission applications.

The three T Level QPL series from Gowanda allow customers immediate access to higher level environmentally screened inductors. This streamlines the customer's operations by eliminating the need to create their own internal upscreening documentation.

Gowanda Electronics now offers these Level T products in addition to its MIL-PRF-27 Level M qualified products initially introduced in 2009. The Level T certification requires more extensive lot conformance testing and inspection than Level M. Each Level T production lot is subjected to 100% thermal shock, burn-in and radiographic inspection in addition to electrical testing. The customer-specific application determines the need to meet Level M or Level T requirements. These series are also suitable for use in non-military high reliability (hi-rel) or high risk applications which warrant a thoroughly tested inductor coil.

Technical specifications for the discrete part numbers within these series address the following ranges:

**MLP5025-T:** Inductance (0.22 to 22000  $\mu$ H); Current Rating (7.00 to .050 Amps); DCR Max (.0080 to 160.0 Ohms)

**MLP1812-T:** Inductance (1.0 to 330  $\mu$ H); Current Rating (1.050 to .090 Amps); DCR Max (.113 to 15.240 Ohms)

**MLP8527-T:** Inductance (1.0 to 18000  $\mu$ H); Current Rating (6.27 to .09 Amps); DCR Max (.009 to 40.0 Ohms)

*continued...*



Gowanda Electronics News Release, 22 February 2012, QPL Inductors for MIL-PRF-27 Level T, p.2/2

Technical information about the three MLP series is available at the company's website.

Data Sheets:

- **MLP5025-T** – <http://www.gowanda.com/files/MLP5025T.pdf>
- **MLP1812-T** – <http://www.gowanda.com/files/MLP1812T.pdf>
- **MLP8527-T** – <http://www.gowanda.com/files/MLP8527T.pdf>

Product Information:

- **MLP5025-T**: [http://www.gowanda.com/products\\_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP5025LevelT](http://www.gowanda.com/products_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP5025LevelT)
- **MLP1812-T**: [http://www.gowanda.com/products\\_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP1812LevelT](http://www.gowanda.com/products_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP1812LevelT)
- **MLP8527-T**: [http://www.gowanda.com/products\\_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP8527LevelT](http://www.gowanda.com/products_qpl/series.asp?o=4&a=8&c=12&sc=80&s=MLP8527LevelT)

All three MLP series utilize high-resistivity, high-saturation ferrite cores, have an operating temperature range of -55°C to +130°C, and are available in tape and reel packaging. Internal connections utilize high melting temperature solder while external terminations are coated with a tin (Sn) lead (Pb) alloy containing more than 3% lead (Pb).

For more information regarding design details, pricing, delivery, or application-specific variations please contact Gowanda Electronics at USA 716-532-2234 or [sales@gowanda.com](mailto:sales@gowanda.com) .

Additional Gowanda Website Links:

- **MLP Series Overview**: [http://www.gowanda.com/products\\_qpl/power\\_surface\\_mount.asp](http://www.gowanda.com/products_qpl/power_surface_mount.asp)
- **QPL Status Chart**: [www.gowanda.com/technical\\_library/qpl\\_progress.asp](http://www.gowanda.com/technical_library/qpl_progress.asp)
- **Environmental Testing Capabilities**: [www.gowanda.com/capabilities/environmental\\_lab.asp](http://www.gowanda.com/capabilities/environmental_lab.asp)
- **News Releases**: [www.gowanda.com/company/news.asp](http://www.gowanda.com/company/news.asp)

QPL Information - Defense Logistics Agency:

- **General Information**: [www.landandmaritime.dla.mil/](http://www.landandmaritime.dla.mil/)
- **MIL-PRF-27**: [www.landandmaritime.dla.mil/Programs/MilSpec/listdocs.aspx?BasicDoc=MIL-PRF-27](http://www.landandmaritime.dla.mil/Programs/MilSpec/listdocs.aspx?BasicDoc=MIL-PRF-27)

###