



Notes:

- Marking: Laser mark, 2 sided
- Packaging: Bulk or Reel

Tape and Reel Specs:

Pcs./12in reel maximum: 2500
 Pitch between parts: 0.20 inches
 Inside tape spacing: 2.062 inches
 Class: 1

[mm]

| | | | | | | | | |
|-------------|---------|---------------------------------|-------------------|-----|---------|--|--|--|
| NEXT ASSEM. | USED ON | LTR | REVISION | BY | DATE | Unless otherwise specified dimensions are in inches. Tolerances on | This drawing or specification is the property of Gowanda Electronics. Copies shall not be reproduced or copied or used as the basis for the manufacture or sale of apparatus without permission. | <div style="border: 2px solid blue; padding: 5px; text-align: center;"> <h2 style="color: green; margin: 0;">Gowanda</h2> </div> |
| | | A | Add mm designator | MM | 9/11/15 | | | |
| Part #: | | ER15M-Dimensional Specification | | | | XX ± .015 XXX ± .010 XXXX ± .005 Angles ± Fractions ± | | ONE MAGNETICS PARKWAY P.O. BOX 111 GOWANDA, NEW YORK 14070 |
| DRAWN BY | MM | Approved By | DP | ENG | QA | MFG | | |
| | | | | | | | | Phone Number: (716) 532-2234 Website: www.gowanda.com |